STUMPJUMPER FSR EXPERT CARBON EVO 650b



HYP GRN/BLK 本カラ の日本国内取り扱いはございません

KEY FEATURES SPECS ALL SPECS ARE SUBJECT TO CHANGE WITHOUT NOTICE. • Hot asymmetrical graphic on the FACT 9m carbon FSR frame with slacker, lower EVO geometry, 150mm of travel, full-cartridge bearing pivots, PF30 BB, and 142mm dropouts makes the meanest trail bike out there FRAME FACT 9m carbon front triangle, EVO geometry. 150mm of travel, full-cartridge PF30 BB, ISCG '05, internal Common PF30 BB, ISCG '05, internal Common PF30 BB, ISCG '05, internal Common addinger and AUTOSAG features 3 compression settings: Climb, Trail and Descend with Trail and rebound adjust REAR SHOCK Custom FOX Float CTD Factory w/ AUT Valve, Kashima coating, and AUTOSAG features 3 compression settings: Climb, Trail and Descend with Trail and rebound adjust • 750mm wide low-rise alloy handlebars control the new RockShox FORK RockShox Pike RC 650b, Solo Air sprint compression and rebound adj., 150mt

- Pike RC fork providing a great blend of stiffness and weight, with great tuning options, 150mm of travel, and a 15mm thru-axle for precise handling
- Lightweight Roval Traverse 142+ All-Mountain wheelset, with DT Swiss internals and spokes, 15mm thru-axle, and a 142+ rear hub spacing for durable, lightweight, and tubeless-ready performance
- 2Bliss Ready Specialized Butcher and Purgatory Control 2.3" tires for premium control on challenging trail conditions
- SRAM's new X0111-speed drivetrain featuring a custom S-2200 carbon crankset with PF30 spindle, single chainring setup works with SRAM X0110-42 cassette for premium shifting and a huge gear range
- All-new, hidden Specialized Command Post IR uses a remote lever to adjust saddle height on-the-fly to maximize climbing and descending performance

PART NO.	DESCRIPTION	COLOR	SIZE

93315-2802	EXPERT CARBON EVO 650B	BILLCARB/	S
50010 2002		MET WHT/BLK	0
93315-2803			N.4
			IVI
93315-2804			L

SPECS	ALL SPECS ARE SUBJECT TO CHANGE WITHOUT NOTICE.
FRAME	FACT 9m carbon front triangle, EVO geometry, FACT IS construction, M5 alloy rear triangle, tapered headtube, carbon PF30 BB, ISCG '05, internal Command Post IR routing, 142mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 150mm travel
REAR SHOCK	Custom FOX Float CTD Factory w/ AUTOSAG and Boost Valve, Kashima coating, Climb, Trail, Descend settings and rebound adj., 195x51mm
FORK	RockShox Pike RC 650b, Solo Air spring, tapered alloy steerer, compression and rebound adj., 15mm thru-axle, 150mm travel
HEADSET	1-1/8 and 1-1/2" threadless, Campy style upper with 1-1/2" lower, cartridge bearings
STEM	Specialized XC, 3D forged alloy, 4-bolt, 6-degree rise, 31.8mm clamp
HANDLEBARS	Specialized All-Mountain, low-rise, 7050 alloy, 750mm wide, 8-degree backsweep, 6-degree upsweep, 31.8mm
GRIPS	Specialized Sip Grip, light lock-on, half-waffle, S/M: regular thickness, Others: XL
FRONT BRAKE	Shimano XT M-785, hydraulic disc, Ice Tech pads, S/M: 180mm rotor, Others: 200mm
REAR BRAKE	Shimano XT M-785, hydraulic disc, Ice Tech pads, S/M: 160mm rotor, Others: 180mm
BRAKE LEVERS	Shimano XT M-785, hydraulic disc
REAR DERAILLEUR	SRAM X01 X Horizon, 11-speed, carbon cage
SHIFT LEVERS	SRAM X01, 11-speed, trigger
CASSETTE	SRAM XG-1195, 11-speed, 10-42
CHAIN	SRAM X1, 11-speed w/ PowerLink
CRANKSET	Custom SRAM S-2200 carbon, PF30 spindle, S: 170mm, Others: 175mm
CHAINRINGS	34T
BOTTOM BRACKET	SRAM, PF30, OS press-in bearings, sealed cartridge
RIMS	Roval Traverse 650b, alloy disc, 28mm wide, 27/32h
FRONT HUB	Roval Traverse 650b, 15mm thru-axle end caps, 27h
REAR HUB	Roval Traverse 142+, XX1 driver body, 12mm thru-axle, 32h
SPOKES	DT Swiss Super Comp, stainless, 2.0/1.65/1.8mm
FRONT TIRE	Specialized Butcher Control, 60TPI, 2Bliss Ready, folding bead, 650bx2.3"
REAR TIRE	Specialized Purgatory Control, 60 TPI, 2Bliss Ready, folding bead, 650bx2.3"
INNER TUBES	Ultralight presta valve
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized Command Post IR, 3-position, internally routed adjustable height w/ air spring, remote operated, single bolt head, 30.9mm, S: 100mm travel, Others: 125mm
SEAT BINDER	Specialized 7050 alloy, single bolt, 34.9mm